



Extreme Performance

The Arqus is designed as the industry's highest performing motion capture camera platform, engineered by the team behind the proven Miqus camera platform. The Arqus line of cameras includes the highest resolution camera in the industry as well as the industry's highest full-FOV frame rate camera.

Advanced marker detection algorithms provide exceptional accuracy. The combined effect of high-resolution image sensors, powerful illumination, and sophisticated algorithms means that small markers can be detected from an impressive distance without sacrificing accuracy.

The unique daisy-chaining of Qualisys systems means a lot less cabling to worry about. The protected line of Arqus cameras is built to withstand any type of weather it may encounter. They are designed to be natively waterproof and dustproof, meaning that no compromise is required.

The Arqus is available in four different models: A5, A9, A12, and A26.

FEATURES

- High-speed motion capture
- Resolution up to 26 MP
- Low latency for real-time applications
- Sun filter¹ and active filtering for outdoor captures
- Water and dust protected housing¹
- Arqus can detect passive markers as far as 50 m (164ft)²
- Passive & active marker support
- Daisy-chaining (no switch required)
- Quick release tripod mount

¹ Optional accessory/feature, not available for all camera models

² Measured with A12 standard, maximum exposure and 19 mm markers

HIGH RESOLUTION-HIGH SPEED-HIGH ACCURACY

The Arqus motion capture camera provides easy to use operation and sports a collection of industry-leading specifications that makes it the highest performing camera in the industry. Performance boils down to resolution, speed and accuracy, all areas where the Arqus excels.

Arqus provides the highest resolution camera in the industry as well as the industry's highest full-FOV frame rate camera. Capture with resolutions ranging from 5MP to 26 MP or with full field-of-view at 1400 fps - surpassing the resolution of any other motion capture camera in the market!

High-resolution image sensors, powerful illumination and sophisticated algorithms renders the Arqus to be the most accurate motion capture camera available, capable of detecting passive markers at up to 50m (164ft)².



Arqus' display shows camera ID and an LED ring provides clear visual communication on camera status.

UP TO 80% LESS CABLING

The unique daisy-chaining of Qualisys camera systems means a lot less cabling to worry about. As an example, a 24-camera Qualisys system covering 30 x 10m (100 x 33ft) will use combined data and power cable, which connects to the next camera in line instead of long cables to connect each camera all the way back to its hub. The end result is 80% less cables!

For portable systems – you will not want anything else. For permanent installation – the cable mess is a thing you won't see in Qualisys labs and studios.



A camera made for outdoor tracking

Qualisys offers cameras built to withstand any weather it may encounter. Protected Arqus models are natively waterproof and dustproof, able to operate in any environments and conditions that you need it to.

Weather protection, combined with embedded active filtering technology, the Sun Filter, and a high-power strobe, which is 50% more powerful than previous models, allows the camera to distinguish markers from the background even in the brightest of sunshine.

Protected models include:

- Weatherproof housing
- Industrial connectors
- Extended temperature range
- Sun filters

All models include:

- Active filtering
- Powerful strobe
- Active marker support



Motorized lens

Control focus and aperture on the Arqus A12 with motorized lenses. The motorized lens is controlled from QTM, our motion capture software.

Low latency

The Arqus platform is engineered for minimum latency & exceptional real-time performance, with camera and full software pipeline latency down to 3 ms.

3D video overlay

Native video camera for the Arqus is the Miquis video, allowing for video overlay which makes analysis results much more intuitive and easy to interpret.

High-speed mode

Full field-of-view, high-speed mode is available on all camera models providing frame rates up to 1400 fps with full field-of-view.

External synchronization

Sync with external hardware and any Qualisys camera using the Camera Sync Unit, which supports Trig in, Sync in/out, Video Genlock, PTP, SMPTE and IRIG

Field of view

Get horizontal field of view of up to 82° with our wide angle lenses or choose from a number of other available field of views for your Arqus selection.

TECHNICAL SPECIFICATIONS

Camera output modes	Marker coordinates / streaming video for preview
Built-in camera display	Graphical high contrast OLED
Marker support	Passive and active
Camera body	Die-cast aluminum, polycarbonate & thermoplastic polyurethane
External Sync	Camera Sync Unit for triggering, hardware sync, Video Genlock, PTP, SMPTE and IRIG
Strobe	24 High power NIR LEDs @ 850nm
Connection	1-connector daisy-chained Gigabit Ethernet and power
Power	Daisy-chained, 36-58 VDC @ 40W maximum
Operating temperature	Standard housing: 0-35°C, (32-95°F) Protected housing: -15-45°C (5-113°F)
Camera size	132 × 143 × 126 mm (5.2 × 5.6 × 5 in)
Camera weight	1.9 kg (4.2 lbs)
Available housing	Standard / Weatherproof housing (IP67/ NEMA 6)
Security attachment	Kensington Lock
Mounting features	Quick release for Manfrotto & Arca swiss, two ¼" camera mounts



Besides the standard 1/4" tripod mounts, Arqus housing has an integrated quick-release plate

Good things come in fours

Four models. Four impressive takes on motion capture. The Arqus platform provides superior resolution, maxed out frame rates and anything in-between.



ARQUS

		A5	A9	A12	A26
Normal mode (full FOV)	Pixels	5 MP	9 MP	12 MP	26 MP
	Resolution	2560 × 1920	4200 × 2160	4096 × 3072	5120 × 5120
	Frame rate	700 fps	290 fps	300 fps	150 fps
High-speed mode (full FOV)	Pixels	1 MP	2.5 MP	3 MP	6.5 MP
	Resolution	1280 × 960	2100 × 1080	2048 × 1536	2560 × 2560
	Frame rate	1400 fps	500 fps	1040 fps	250 fps
Field of View (FOV)	Standard	56° × 44°	67° × 37°	54° × 42°	56° × 56°
	Wide angle FOV	77° × 62°	82° × 48°	70° × 56°	77° × 77°
	Narrow angle FOV	29° × 22°	47° × 25°	31° × 24°	29° × 29°
Max frame rate (reduced FOV)		10 000 fps	10 000 fps	10 000 fps	10 000 fps
Measurement distances with 16 mm markers		26m (85ft)	TBD	40m (130ft)	TBD
Active filtering (improved outdoor support)		Yes	Yes	Yes	Yes
Motorized lens		No	No	Yes	No
Lens mount		C	C	EF-M	C

QUALISYS



qualisys.com

sales@qualisys.com

Qualisys Europe

Gothenburg, Sweden

Qualisys Americas

Chicago, USA

Qualisys Asia Pacific

Shanghai, China